



Corus Colorsteels

Aquatite® Frequently Asked Questions

Corus Colorsteels has unrivalled experience in the handling and usage of Aquatite®. The Frequently Asked Questions and answers included here reflect some of the most common enquiries that we receive.

“Where can I get Safety datasheets for Aquatite products?”

Datasheets for both **Aquatite TPO** and **Aquatite PVC** are available on request from Corus Colorsteels and can be downloaded from www.corusservicecentres.com/aquatite

“Is Aquatite compatible with other products?”

Aquatite TPO is normally compatible with other TPO membranes. To discuss a specific project or application please contact info@sandene.co.uk or call +44 (0) 01969 625000

Aquatite PVC is compatible with all other PVC membranes and can be joined easily to Plastisol products

“What is the best way to weld Aquatite?”

Aquatite TPO can be hot air welded at temperatures between 300°C to 400°C. It is recommended that PID welding equipment be used to ensure a constant temperature is maintained. For specific guidance, please contact info@sandene.co.uk or call +44 (0) 01969 625000

Aquatite PVC should be hot air welded at temperatures > 400°C. More detailed instructions can be found in the welding datasheet which is available from Corus Colorsteels or from www.corus-servicecentres.com/aquatite.

“Can Aquatite products be welded using any other techniques?”

Aquatite TPO is not suitable for use with other welding techniques.

Aquatite PVC can be chemically bonded but its success is dependant upon attaining the correct temperature and the type of solvents used. Tetrahydrofurane can be used but it requires handling with care.

“Are Aquatite products covered by a guarantee?”

Only the 1200 micron systems comes with the reassurance of a leading guarantee. **Aquatite TPO** is guarantee for 20 years, with an expected life-span of 25, whilst the **Aquatite PVC** comes with a 15 year guarantee and an expected life-span of 20.

“Are the guarantees transferable?”

Yes,. Should the ownership of the building change, the Aquatite guarantees can be transferred to the new owner.

“How do I register my Aquatite guarantee?”

Simply complete and return the guarantee registration card, which is available from Corus Colorsteels or via www.corus-servicecentres.com/aquatite, within three months of completion of the installation.

“What colours are Aquatite products available in?”

Aquatite TPO comes in a standard colour mouse grey. Other colours are available, but are subject to minimum order levels.

Aquatite PVC is available in grey only.

“What physical testing criteria cover Aquatite products?”

Both **Aquatite TPO** and PVC are covered by BS 3900/E2.

“What sizes are available?”

A full range of standard sizes of both products is available ex-stock. Other sizes can be supplied to order. Please refer to Corus Colorsteels for details of ex-stock sizes and lead times on other sizes.

“Are any accessories available for use with Aquatite products?”

A full range of accessories is available for use with **Aquatite TPO**. For more details, please contact info@sandene.co.uk or call +44 (0) 01969 625000

Joining straps and wide rolls can be supplied for use with **Aquatite PVC**. Please contact Corus Colorsteels to discuss your requirements in more detail.

Corus Colorsteels

North Blackvein Industrial Estate, Islwyn Road, Cross Keys, South Wales NP11 7YD
T +44 (0) 1495 279100 F +44 (0) 1495 271456

E aqatite@corusgroup.com www.corus-servicecentres.com/aquatite