



- NOTES:**
1. RATE OF CHANGE OF SET-BACK MUST NOT EXCEED 1 in 16.
  2. SEE DRAWINGS VL00 & VL01 FOR DETAILS ON THE DETERMINATION OF SET-BACK AND WORKING WIDTH.
  3. AREA USED BY PEDESTRIANS TO BE HARD STANDING.
  4. DESIRABLE DISTANCE BETWEEN THE TWO BARRIERS IS 1300MM, HOWEVER, IF EITHER BARRIER HAS A WORKING WIDTH GREATER THAN 1300MM THEN THE MINIMUM DISTANCE SHALL BE EQUAL TO THE GREATER WORKING WIDTH.
  5. ABC TERMINALS CAN ONLY BE FITTED TO N2 BARRIER SYSTEMS WITH A WORKING WIDTH OF W2 TO W4.

Rev No	Revision Notes	Rev. Date	By
4	Note 5 modified	08/02/08	R.P
3	Note 4 & 5 modified	18/12/08	R.P
2	Minimum full height was 10m	13/12/08	R.P

**Corus Distribution  
& Building Systems**



**COFUS**  
CORUS CORP. ILLANWERN WORKS  
NEWPORT, S. WALES, UK, NP19 4QZ

Sales tel: +44 (0) 1633 290011 Fax: +44 (0) 1633 464508  
 Technical tel: +44 (0) 1633 752100 Fax: +44 (0) 1633 464508  
 © Corus email: [sales@corusgroup.com](mailto:sales@corusgroup.com)

<b>DESCRIPTION</b>		<b>PEDESTRIAN CROSSING POINT</b>	
<b>CUSTOMER</b>			
<b>PRODUCT</b>	VETEX	<b>DRG. No.</b>	SH. REV.
<b>DATE</b>	31/08/05	<b>VL06</b>	1 4
<b>DRAWN</b>	MAH CHECKED AMR		
<b>SCALE</b>	NTS		