



- NOTES:**
1. FOR DEFINITIONS OF SETBACK AND WORKING WIDTH SEE DRAWING VL00 & VL01.
 2. POSTS MORE THAN 4.5m FROM EDGE OF CARRIAGEWAY, HARD SHOULDER OR HARD STRIP MAY REQUIRE NORMAL CONTAINMENT PROTECTION.
 3. ON SINGLE CARRIAGEWAY ROADS AND PLANNED CONTRAFLOW APPLICATIONS, THE DEPARTURE LAYOUT SHOULD MATCH THE APPROACH LAYOUT.
 4. ON ROADS 50 M.P.H. OR GREATER P4 MUST BE USED FOR LEADING TERMINALS.

**Corvus Distribution
& Building Systems**

CORVUS GEP, LLANWERN WORKS
NEWPORT, S. WALES, UK, NP19 4QZ

Sales tel: +44 (0) 1633 290011 Fax: +44 (0) 1633 464508
 Technical tel: +44 (0) 1633 752100 Fax: +44 (0) 1633 464508
 © Corvus email: sales@cds@corvusgroup.com

Rev No	Revision Notes	Rev. Date	By
4	Overall dimension method changed	18/12/08	R.P
3	Note 5 removed	18/12/08	R.P
2	Dimension 10.5m was 12m	19/12/08	R.P

DESCRIPTION	H2 SINGLE SIDED - VERGE OR CENTRAL RESERVATION
CUSTOMER	
PRODUCT	Vetex
DATE	17/02/06
DRAWN	MAH CHECKED MRL
SCALE	NTS
DRG. No.	SH. REV.
VL08	1 4