



- NOTES:**
- FOR DEFINITIONS OF SETBACK AND WORKING WIDTH SEE DRAWING VL00 & VL01.
 - POSTS/STRUCTURES MORE THAN 4.5 M FROM EDGE OF CARRIAGEWAY, HARD SHOULDER OR HARD STRIP MAY NOT REQUIRE NORMAL CONTAINMENT PROTECTION.
 - SYSTEM PROGRESSION TO BE WITHIN LENGTH L1.
 - ON SINGLE CARRIAGEWAY ROADS AND PLANNED CONTRAFLOW APPLICATIONS, THE DEPARTURE LAYOUT SHOULD MATCH THE APPROACH LAYOUT.
 - MINIMUM LENGTH OF FULL HEIGHT SAFETY FENCE IS 37.5 METRES PLUS TERMINALS.
 - ON ROADS 50 M.P.H. OR GREATER P4 MUST BE USED ON LEADING TERMINALS.
 - ABC OR X-TENSION TERMINALS CAN ONLY BE FITTED TO N2 BARRIER SYSTEMS WITH A WORKING WIDTH OF W2 TO W4.

WORKING WIDTH (mm)	SAFETY FENCE CODE FENCE TYPE			
	L1	L2	L3	L4
1701 +	W5			
1301 - 1700	L1	L2	L3	L4
	W5			
1001 - 1300	L1	L2	L3	L4
	W4*			
	L1	L2	L3	L4
801 - 1000	W3*			
	L1	L2	L3	L4
	W2			

* SEE NOTE 3



**Corus Distribution
& Building Systems**

CORUS CB, ILANVERN WORKS
NEWPORT, S. WALES, UK, NP19 4QZ

Sales tel: +44 (0) 1633 290011 Fax: +44 (0) 1633 464508
Technical tel: +44 (0) 1633 752100 Fax: +44 (0) 1633 464508
Corus email: sales@corusgroup.com

Rev No	Revision Notes	Rev. Date	By
6	Note 7 modified	14/01/10	A.B.
7	Note 7 modified	08/02/08	R.P
8	L2 was 10m and note added ref. L1	18/12/08	R.P

DESCRIPTION VERGE N2 SINGLE SIDED - FENCE LAYOUT.

CUSTOMER			
PRODUCT	VETEX		
DATE	31/08/05		
DRAWN	MAH	CHECKED	MRL
SCALE	NTS		
DRG. No.	VL03		
SH. REV.	1 8		