


- NOTES:
- SPECIAL CONCRETE FOUNDATIONS TO BE CONSTRUCTED TO THE DIMENSIONS DESCRIBED IN THE CONTRACT.
 - CONCRETE TO BE MIX STR/C25 UNLESS OTHERWISE DESCRIBED IN THE CONTRACT.
 - ALL DRIVEN, EXCAVATED AND SOCKETED FOUNDATIONS ARE TO BE PROVEN BY PUSH / PULL TESTING. THE 160 X 49 POST MUST ACHIEVE A BENDING MOMENT OF 8000 Nm WITHOUT THE DEFLECTION EXCEEDING 100mm.
 - SUGGESTED CORE DIAMETER FOR THIS POST IS Ø250.

ALTERNATIVE INTERMEDIATE POSTS FOUNDATIONS AND FIXINGS

Rev. No	Revision Notes	Rev. Date	By
8	Note 3 Modified, Note 4 Added & A419 Post Added	01/02/08	R.P.
7	C301 Beam removed	18/02/07	R.P.
6	80mm dimension added	06/01/07	R.P.
5	Note 3 modified, A455 & A458 removed from the drawing	18/12/06	R.P.
4	A419 Post Removed	01/11/06	R.P.
3	Note 3 added	26/10/06	R.P.
2	Ø350 concrete changed to 310 sq in 2 areas	18/10/06	R.P.
1	A455 and A458 posts added.	13/10/06	R.P.

Corus Distribution & Building Systems

CORUS GB, LLANWERN WORKS
NEWPORT, S. WALES, UK, NP19 4QZ



Sales tel: +44 (0) 1633 290011 Fax: +44 (0) 1633 464508
Technical tel: +44 (0) 1633 752100 Fax: +44 (0) 1633 464508
© Corus email: sales@corusgroup.com

DESCRIPTION	CUSTOMER	PRODUCT	DATE	DRAWN	SCALE	DRG. No.	SH. REV.
General Arrangement - 160 x 49 Posts	Vetex		26/06/06	RJ	CHECKED MRL	VGA02	1 8