



- NOTES:**
- FOR DETAILS OF ALTERNATIVE POSTS, FOUNDATIONS AND FIXINGS SEE DRG.No. VGA0 2
  - THIS TYPE OF BARRIER SHALL NOT BE USED WHERE THE FULL HEIGHT LENGTH (EXCLUDING P1's & P4's) IS LESS THAN 2M.
  - THIS TYPE OF BARRIER SHALL NOT BE USED ON CURVES OF RADIUS LESS THAN 100m. FOR RADIUS LESS THAN 100m CONTACT CORUS CEP.
  - WHERE A KERB IS REQUIRED THE PREFERRED HEIGHT IS 75mm. MAX KERB HEIGHT IS 125mm.

Rev No	Revision Notes	Rev. Date	By
3	Note added relating the standard socket length, note 2 modified, note 3 & 4 added	20/10/08	R.L.
2	Drawing Revisions	19/10/08	R.L.
1	First View Released	24/04/08	R.L.

**Corus Distribution & Building Systems**

CORUS CEP, LLANWERN WORKS  
NEWPORT, S. WALES, UE, NP19 4QZ



**CORUS**

Sales tel: +44 (0) 1633 290011 Fax: +44 (0) 1633 464508  
Technical tel: +44 (0) 1633 752100 Fax: +44 (0) 1633 464508  
© Corus email: safeforced@corusgroup.com

DESCRIPTION	N2 W2 1.6M CTRRS SINGLE SIDED		
CUSTOMER	VETEX		
PRODUCT	VETEX		
DATE	23/01/06		
DRAWN	MAH	CHECKED	MRL
SCALE	NTS		
DRG. No.	VGA120		SH. REV. 1 3