



- NOTES:**
- FOR DETAILS OF ALTERNATIVE POSTS, FOUNDATIONS AND FIXINGS SEE DRG No. VGA0 2
 - THIS TYPE OF BARRIER SHALL NOT BE USED WHERE THE FULL HEIGHT LENGTH (EXCLUDING P1's & P4's) IS LESS THAN 20M.
 - THIS TYPE OF BARRIER SHALL NOT BE USED ON CURVES OF RADIUS LESS THAN 50m. FOR RADIUS LESS THAN 50m CONTACT CORUS CEP.
 - WHERE A KERB IS REQUIRED THE PREFERRED HEIGHT IS 75mm. MAX KERB HEIGHT IS 125mm.



Corus Distribution & Building Systems

CORUS CEP, LLANWERN WORKS
NEWPORT, S. WALES, UK, NP19 4QZ

CORUS

Sales tel: +44 (0) 1633 290011 Fax: +44 (0) 1633 464508
Technical tel: +44 (0) 1633 752100 Fax: +44 (0) 1633 464508
© Corus email: safecoad@corusgroup.com

DESCRIPTION	N2W3 2.5m CTRS SINGLE SIDED		
CUSTOMER	Vetex		
PRODUCT	Vetex		
DATE	26/06/06		
DRAWN	RJ	CHECKED	MRL
SCALE	NTS		
DRG. No.	VGA130		SH. REV.
	1		3

Rev. No	Revision Notes	Rev. Date	By
3	Note added advising the standard Socket length, note 2 modified, notes 3 & 4 added	20/12/06	R.P.
2	Drawing Redrawn	16/10/06	R.P.