



ELEVATION OF END TERMINAL

NOTES:

1. FOR DETAILS OF ALTERNATIVE POSTS, FOUNDATIONS AND FIXINGS SEE DRAWINGS NUMBERS VGA200 & VGA202.
2. FENCE ASSEMBLY SHOWN IS FOR USE IN VERGE ASSEMBLY - CENTRAL RESERVE IS THE SAME BUT HAS REVERSED POST ORIENTATION.
3. WHEN THIS TERMINAL IS USED TO TERMINATE AN N2 SYSTEM, THE FIRST FULL HEIGHT BEAM MUST HAVE POSTS SPACED AT N2 W2, W3 OR W4.
4. THIS TYPE OF END TERMINAL SHALL NOT BE USED WHERE THE LENGTH BETWEEN END POSTS IS LESS THAN 44m OR ON CURVES OF RADII LESS THAN 50m. FOR RADII LESS THAN 50m CONTACT CORUS CEP.
5. P1 END TERMINALS ARE SUITABLE FOR USE ON LEADING AND TRAILING ENDS OF BARRIER ON ROADS BELOW 50 MPH. ON ROADS 50 MPH AND ABOVE THE P1 END TERMINAL CAN ONLY BE USED ON THE TRAILING END.
6. GENERAL LAYOUT IS SYMMETRICAL FOR APPROACH AND DEPARTURE ENDS.

Rev No	Revision Notes	Rev. Date	By
3	Note 3 modified W2 & W3 added	20/12/06	R.P.
2	Note 3 modified dimension removed and working width added	08/12/06	R.P.
1	Redrawn	21/1/06	R.P.

Corus Distribution & Building Systems



CORUS CEP, LLANYBYR WORKS  
NEWPORT, S. WALES, UK, NP19 4QZ

Sales tel: +44 (0) 1633 290011 Fax: +44 (0) 1633 464508  
Technical tel: +44 (0) 1633 752100 Fax: +44 (0) 1633 464508  
Corus email: safecoads@corusgroup.com

DESCRIPTION		P1 END TERMINAL (CONCRETED POSTS)	
CUSTOMER			
PRODUCT	SAFETY BARRIER		
DATE	05/07/06		
DRAWN	R.J.	CHECKED	
SCALE	NTS		
DRG. No.		SH.	REV.
VGA201		1	3