



- NOTES:
1. FOR DETAILS OF ALTERNATIVE POSTS, FOUNDATIONS AND FIXINGS SEE DRG No. VGA01
 2. THIS TYPE OF BARRIER SHALL NOT BE USED WHERE THE FULL HEIGHT LENGTH (EXCLUDING P1's & P4's) IS LESS THAN 20M.
 3. THIS TYPE OF BARRIER SHALL NOT BE USED ON CURVES OF RADIUS LESS THAN 50m. FOR RADIUS LESS THAN 50m CONTACT CONUS CEP.
 4. WHERE A KERB IS REQUIRED THE PREFERRED HEIGHT IS 75mm. MAX HEIGHT IS 125mm.

Tata Construction
Products



TATA CP, LLANWERN WORKS
NEWPORT, S. WALES, UK, NP19 4QZ

Sales tel: +44 (0) 1633 290011 Fax: +44 (0) 1633 464508
 Technical tel: +44 (0) 1633 752100 Fax: +44 (0) 1633 464508
 © Tata email: sales@tatasteel.com

DESCRIPTION NZW5 5m CTRS SINGLE SIDED

CUSTOMER

PRODUCT

DATE

DRAWN

SCALE

Veter

29/07/05

MAH

NTS

DRG. No.

VGA41

SH. REV.

1 10

Rev. No	Revision Notes	Rev. Date	By
10	Beam view changed. Company details changed.	27/01/11	A.B.
9	Note added advising the standard Socket length, note 2 modified, notes 3 & 4 added	08/12/06	R.P.
8	Drawing Redrawn	13/10/06	R.P.
7	Uncontrolled Copy Note Added	24/04/06	R.L.

On flat ground, the standard length socket (A70S) for use with an A218 post is 380 mm's long.