



The Span Tables below have been created in accordance BS5950 Part 6. The values are based on a maximum permitted deflection of Span/120.

Safe imposed (positive) loads (kN/m²)

Span condition	Span (m)														
	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.0	2.1	2.2	2.3	2.4	2.5	2.6
Single	3.55	3.00	2.58	2.23	1.95	1.72	1.53	1.37	1.23	1.12	1.02	0.93	0.85	0.78	-
Double	2.70	2.37	2.09	1.87	1.67	1.51	1.37	1.25	1.14	1.05	0.96	0.89	0.83	0.77	-
Multi	3.25	2.86	2.53	2.26	2.03	1.83	1.66	1.51	1.39	1.27	1.18	1.09	1.01	0.94	0.88

Safe wind suction (negative) loads (kN/m²)

Span condition	Span (m)														
	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.0	2.1	2.2	2.3	2.4	2.5	2.6
Single	3.41	2.90	2.50	2.18	1.92	1.70	1.51	1.36	1.23	1.11	1.01	0.93	0.85	0.79	-
Double	3.26	2.78	2.39	2.09	1.83	1.62	1.45	1.30	1.17	1.06	0.97	0.89	0.81	0.75	-
Multi	4.07	3.47	2.99	2.61	2.29	2.03	1.81	1.63	1.47	1.33	1.21	1.11	1.02	0.94	0.87