

NUMBER OF SAB SANDWICH PANELS PRO TYPE AND PACK

			Old		Per 1-11-2014	
Type	Stacking method	Thickness (mm)	Max. number	Packheight (incl. packaging)	Max. number @	New packheight (incl. packaging)
SAB W 40.1150	A/A * of B/B #	40	26	1190	27	1200
SAB W 60.1150	A/A * of B/B #	60	17	1170	18	1200
SAB W 80.1150	A/A * of B/B #	80	13	1190	13	1160
SAB W 100.1150	A/A *	100	10	1150	10	1120
SAB W 120.1150	A/A *	120	8	1110	9	1200
SAB W 150.1150	A/A *	150	7	1200	7	1170
SAB W 120.1150 EI30	A/A *	120	8	1110	9	1200
SAB W 150.1150 EI30	A/A *	150	7	1200	7	1170
SAB W 95.1020 TL (EI15)	A/B *	95	11	1195	11	1195
SAB W 135.1020 TL (NEW)	A/B *	135	7	1095	8	1200
SAB W 80.1000 SL	A/B *	80	15	1215	15	1215
SAB W 100.1000 SL (NEW)	A/B *	100	12	1002	12	1002
SAB WB 60.1000	A/A * of B/B #	60	17	1170	18	1200
SAB WB 80.1000	A/A *	80	13	1190	13	1160
SAB WB 80.1000	B/B #	80	13	1190	13	1160
SAB WB 100.1000	A/A *	100	10	1150	10	1120
SAB WB 120.1000	A/A *	120	8	1110	9	1200
SAB WB 80.1000 EW30	A/A*	80	13	1190	13	1160
SAB WB 80.1000 EW30	B/B #	80	13	1190	13	1160
SAB WB 100.1000 EW30	A/A *	100	10	1150	10	1120
SAB WB 120.1000 EW30	A/A*	120	8	1110	9	1200
SAB D 75.1000	A/B #	75	18	1155	18	1155
SAB D 75.1000	A/A * of B/B #	75	14	1170	14	1170
SAB D 95.1000	A/B #	95	13	1175	14	1205
SAB D 95.1000	A/A * of B/B #	95	11	1195	11	1165
SAB D 115.1000	A/B #	115	10	1125	10	1095
SAB D 115.1000	A/A * of B/B #	115	9	1185	9	1155
SAB D 135.1000	A/B #	135	8	1060	9	1195
SAB D 135.1000	A/A *	135	7	1095	8	1200

Total maximum packheight (including packaging) = 1200 mm

@ Maximum number of panels per package depends on length of the panels, partly because package maximum weight of 2,500 kg should not exceed

* standard pack stacking

stacking possible on request

From 1/1/2012 SAB no longer produce RockPro mineralwool panels

Stand: October 2014